

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
9 June 2005 (09.06.2005)

PCT

(10) International Publication Number
WO 2005/051563 A1

(51) International Patent Classification⁷: **B21D 43/05**,
43/10, B30B 15/00

(74) Agents: **ROSHARDT, Werner, A. . et al.**; Keller &
Partner Patentanwälte AG, Schmiedenplatz 5, Postfach,
CH-3000 Bern 7 (CH).

(21) International Application Number:
PCT/CH2004/000710

(22) International Filing Date:
25 November 2004 (25.11.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PCT/CH03/00780
25 November 2003 (25.11.2003) CH

(71) Applicant (for all designated States except US): **GÜDEL
GROUP AG** [CH/CH]; c/o Güdel AG, Gaswerkstrasse 26,
CH-4900 Langenthal (CH).

(72) Inventors; and


(75) Inventors/Applicants (for US only): **HEID, Rudolf**
[CH/CH]; Dr. Probst-Strasse 11, CH-4542 Luterbach
(CH). **KURT, Hans-Ulrich** [CH/CH]; Moosackerstrasse
17, CH-4566 Kriegstetten (CH). **LEHMANN, Ulrich**
[CH/CH]; Bleichestr. 24B, 4900 Langenthal (CH).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LU, MC, NL, PL, PT, RO, SE,
SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: CONVEYOR FOR TRANSPORTING WORK PIECES IN A PRESS



(57) Abstract: A conveyor for transporting work pieces in a press, in particular a press line or multiple-die press, from a first station to a second station adjacent to the first station, comprises at least one lateral beam (300, 400) arranged on a side of the press, essentially extending parallel to a transport direction of the conveyor (52), at least one bar (500) having grippers (502) for gripping the work piece to be transported, whereby the bar (500) is attached to the lateral beam (300, 400) in such a way that it is movable along a longitudinal extension of the beam (300, 400); and for each lateral beam (300, 400) an assembly (100, 200) for supporting the lateral beam (300, 400). The assembly (100, 200) comprises a pivoting mechanism (106, 107, 108, 109, 301, 302) for pivoting the lateral beam (300, 400) around a horizontal pivotal axis perpendicular to the transport direction, and the grippers (502) are rotatably movable for at least compensating a change of orientation of the work piece due to the pivoting of the lateral beam (300, 400).



Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.